

COLOR Tracciante Professionale

Fluorescent tracer paint

DESCRIPTION

Modified acrylic based paint, for temporary demarcation. Fluorescent effect.

AREAS OF APPLICATION

For temporary marking in the construction and construction industry. Can also be used in the forestry sector. It adheres excellently even to damp surfaces

FEATURES

- For all surfaces: masonry, asphalt, wood, lawn, etc.
- High resistance to wear and atmospheric agents
- Self-cleaning valve
- 360° dispensing

TECHNICAL DATA

Colour	Yellow, red, green, blue, white
Gloss	25-30 gloss
Dust-free time /20°C [min]	Ca. 10
Skin time /20°C [min]	Ca. 30
Drying time /20°C [ore]	24
Medium Yield per cylinder [m ² /600ml]	1,3 – 1,6

APPLICATION

Shake well before use (at least 2 minutes). Spray at a distance of about 25 cm, in several layers until the desired effect is obtained; for a possible second coat wait about 5 minutes.

WARNINGS

Product classified as dangerous (see relevant Safety Data Sheet).

Adv. Specifications: Pressurized container. Protect from sunlight and do not expose to higher temperatures at 50°C. Do not pierce or burn after use.

Do not spray on a flame or incandescent body.

PACKAGING

600 ml cylinder

6 pieces per box

STORAGE AND SHELF LIFE

Color Tracing Professionale can be stored for 24 months from the date of production, in intact containers and in dry, cool environments.

GENERAL INFORMATION

The information contained in this technical sheet represents the best of our knowledge. In any case, this document cannot be considered a guarantee of use, sector of use and application of the product in accordance with the instructions provided. The success of the application is beyond our control and depends on numerous factors. We decline any responsibility for improper use of the product, the recommendations contained in this document should be considered general guidelines. If doubts remain, carry out preliminary tests. NPT Srl reserves the right to modify and update the technical data sheet without notice. Customers are kindly requested to verify that they have the latest version.

ALWAYS CONSULT THE SAFETY DATA SHEET BEFORE USING THE PRODUCT