

GRASSO PER NAUTICA

Special grease based on calcium, zinc and titanium oxides and special thickeners

DESCRIPTION

The product is a very adhesive and highly water-repellent pomatous grease. Good resistance to both fresh and salt water, it has excellent anti-corrosion properties (from saltiness).

AREAS OF APPLICATION

Lubricates and protects on-board equipment, suitable for the lubrication of joints, sleeves, undersheath cables, engines including outboard ones, tie rods, linkages, steering systems, etc. For protection from saltiness of all types on-board equipment.

FEATURES

- Lubricates and protects on-board equipment
- Good stability in fresh and salt water
- High adhesion
- Anti-corrosion protectant for salt spray

TECHNICAL DATA

Colour	White
Appearance	Pomato paste
Specific gravity [g/cm ³] (NPT Method 06) (23°C and 50% RH)	0.9
Consistency (NLGI)	2
Manipulated penetration (ASTM D217)	265 ÷ 295
Viscosity 40°C base oil [mm ² /s] (ASTM D445)	90 ÷ 110
Dropping point (ASTM D556)	145
Max operating temperatures [°C]	100
Water washout [%] (79°C, 1 h ASTM D1264)	Max 4

APPLICATION

The surfaces must be clean, free of residues (dust, rust); the presence of other lubricants can alter the adhesiveness.

CLEANING OF EQUIPMENT AND PERSONAL PROTECTION

It can be removed using paper or cloth. Clean the tools used with mineral spirits. If he enters a contact with skin, simply remove and wash with soap and water.

PACKAGING

Bottle 125 ml 12 pieces for box

STORAGE AND SHELF LIFE

The product is stable in its original packaging. Storage temperature below 25°C in a cool, dry place.

GENERAL INFORMATION

The information contained in this data sheet represents the best of our knowledge. However, this document cannot be regarded as a guarantee that the product will be used and applied in accordance with the instructions provided. Successful application is beyond our control and depends on many factors. We accept no responsibility for the misuse of the product, the recommendations in this document should be considered general guidelines. If any doubts remain, please carry out preliminary tests. NPT Srl, reserves the right to modify and update the data sheet without prior notice. Customers are kindly requested to check that they have the latest version.

ALWAYS CONSULT THE SAFETY DATA SHEET BEFORE USING THE PRODUCT