

ULTRA F5

Super multifunctional professional spray

DESCRIPTION

State-of-the-art technical spray product with an unlocking, water-repellent, lubricant protective and degreasing function for mechanical parts in general. Its unique multifunctionality makes it an ideal partner ideal partner in work and every day working.

AREAS OF APPLICATION

It has innumerable applications thanks to its strong penetrating and unlocking power, it is an excellent lubricant, it eliminates current leakage by expelling moisture and preventing short circuits. It stops or prevents corrosion, even in a salty environment, dissolves rust, protects and lubricates padlocks, locks mechanical parts of cars, motorbikes, bicycles, electronic components of motors, household appliances, switches, hinges. Easily removes grease, tar and glue from metal or plastic surfaces; keeps efficient switches and mechanical equipment operating outdoors. Ideal in the workshop and bricolage, boating, for the maintenance of motorbikes, bicycles, skates and reels, agricultural machinery and household appliances in general.

FEATURES

- Release agent against oxidation and rust
- Water repellent
- For electronics and electrical engineering
- Lubricant
- Protective, forms an antioxidant film
- Removal of stubborn dirt
- Ideal for marine

TECHNICAL DATA

Appearance	Liquid
Colour	Brown
Specific gravity [g/cm³] (NPT Method 06) (23°C and 50% RH)	Ca. 0.64
Flash Point [°C]	< - 50

Flash Point [°C] (liquid phase)	> 55
Solubility	In organic solvent
Loading pressure [bar]	3.2
Application temperature [°C]	5 ÷ 30

APPLICATION

Shake well before use. The 'Multiposition' valve allows 360° dispensing. The special straw spout allows both a direct and precise spray as well as the classic 'fan' spray. Spray the product from a distance of approx. 20 cm, at short intervals on the area to be treated, leaving it to act for a few minutes and allow deep penetration.

CLEANING OF EQUIPMENT AND PERSONAL PROTECTIVE MEASURES

Take care when handling and using the product, use disposable protective gloves. In case of skin contact, simply wash with soap and water.

PACKAGING

400 ml canister	24 pieces per box
500 ml cylinder	24 pieces per box
200 ml cylinder	24 pieces per box

STORAGE AND SHELF LIFE

The product can be stored for 18 months in its original packaging. Storage temperature between 5°C to 30°C in a cool, dry place. Keep away from sources of moisture, heat and direct sunlight.

GENERAL INFORMATION

The information contained in this data sheet represents the best of our knowledge. However, this document cannot be regarded as a guarantee that the product will be used and applied in accordance with the instructions provided. Successful application is beyond our control and depends on many factors. We accept no responsibility for the misuse of the product, the recommendations in this document should be considered general guidelines. If any doubts remain, please carry out preliminary tests. NPT Srl, reserves the right to modify and update the data sheet without prior notice. Customers are kindly requested to check that they have the latest version.

ALWAYS CONSULT THE SAFETY DATA SHEET BEFORE USING THE PRODUCT