

Technical data sheet Bitum gasket spray  
Ver. 2.0 October 2023

# BITUM GASKET SPRAY

## Bitumen protective waterproofing spray

### DESCRIPTION

Bitum Gasket Spray is the ideal waterproofing agent for protecting, bonding and preserving porous and non-porous materials. The product is overpaintable and adheres to all materials. This waterproofing spray is suitable for a wide variety of uses: underground piles, terracotta pots, flashings and sheets, roofing, fibre cement tiles, gutters, chimneys and skylights, cracks in walls.

### FEATURES

- Adheres to all materials
- Waterproofs and seals
- Prevents corrosion and ageing
- Overpaintable

### TECHNICAL DATA

<b>Appearance</b>	Liquid (spray)
<b>Specific gravity</b> [g/cm <sup>3</sup> ] (NPT Method 06) (23°C and 50% RH)	Ca. 0.71
<b>Flash point</b> (°C)	<0 (propellant)
<b>Can pressure</b> [bar]	3.2
<b>Solubility</b>	In solvent
<b>Application temperature</b> [°C]	5 ÷ 30
<b>Drying times (1)</b> [h]	6
<b>Medium yield (2)</b> [m <sup>2</sup> ]	4

(1) Depending on thickness, surface type and environmental conditions

(2) Depending on thickness

## APPLICATION

---

Make sure that loose parts, crumbly or non-adherent parts, paint, rust, dust, release oils and carefully clean the surfaces which must be solid and dry. Shake the can well, spray on the desired part at a distance of approx. 20 cm, intermittently, so as to maintain an even spray pattern. For proper functioning, shake the can every 2/3 sprays. Once the application is finished turn the can upside down and spray for 1-2 seconds so that the nozzle remains clean and does not become clogged.

## PACKAGING

---

500 ml cylinder          6 pieces per box

## STORAGE AND SHELF LIFE

---

Bitum Gasket Spray can be stored for 18 months in the original packaging. Storage temperature between 5°C and 30°C in a cool, dry place. Keep away from sources of humidity, heat sources and from direct contact with sunlight.

## GENERAL INFORMATION

---

The information contained in this data sheet represents the best of our knowledge. However, this document cannot be regarded as a guarantee that the product will be used and applied in accordance with the instructions provided. Successful application is beyond our control and depends on many factors. We accept no responsibility for the misuse of the product, the recommendations in this document should be considered general guidelines. If any doubts remain, please carry out preliminary tests. NPT Srl, reserves the right to modify and update the data sheet without prior notice. Customers are kindly requested to check that they have the latest version.

ALWAYS CONSULT THE SAFETY DATA SHEET BEFORE USING THE PRODUCT